

## TRANSDUCER VERSATORR

BIBVT100

Brooks Transducer BVT100

- Type: Pirani Transducer
- Temperatur: Ambient -50°C
- Tryk område: 7.5x10<sup>-7</sup> Torr igennem 1000 Torr
- Digital kommunikation: RS-232 /// RS-485



### PRODUKTBESKRIVELSE

Software findes her. <https://www.brooksinstrument.com/en/products/accessories-software/product-software/versatorr-gui>

### SPECIFIKATIONER

<b>Funktion</b>	Vakuüm måler
<b>Trykområde max</b>	10 bar
<b>Analog output</b>	0.5 - 9.5 Vdc, 1.0-9 Vdc, 0.375 - 5.659 Vdc, 1.9 - 10 Vdc, 1.5 - 8.5 Vdc. 1.9 - 9.1 Vdc, 0-10Vdc, 0-5Vdc
<b>Digital output</b>	RS232, RS485
<b>Temperaturområde fra</b>	-20 °C
<b>Temperaturområde til</b>	50 °C
<b>Tilslutning</b>	Flange DN16KF, DN25KF, VCR8F
<b>Medietemperatur fra</b>	-20 °C
<b>Nøjagtighed</b>	±0.25% of reading
<b>Medietemperatur til</b>	85 °C
<b>Certifikater</b>	UL, CSA, EN/IEC, CE, RoHS
<b>Elektrisk tilslutning</b>	9-Pin SUB-D Male, 15-Pin HD SUB-D Male, 6-Pin Hirschmann, 8-Pin RJ45 / FC68