

## DIAPHRAGM MÅLEVENTIL

### DMV-SERIEN Diaphragm Metering Valve

- Normalt tryk: 20 bar
- Flowrange: 0-20 l/min
- CV: 0.024
- Leak: <10<sup>-9</sup> mbar l/s
- Temperaturområde: -20 til 70°C



## PRODUKTBESKRIVELSE

### Tescom Diaphragm Måleventil

Giver en præcis flowkontrol af højrenheds-gasser i point-of-use-samlinger eller i kombination med trykregulatorer.

### Applikationer

- Kontrol af flowet af procesmedier med høj præcision
- Laboratorie-, R&D- og analyseapplikationer
- Egnede til ECD (Electronic Capture Detector) applikationer

### Fordele

- Præcis kontrol af flow
- Næsten lineær flowkarakteristik
- Metal-til-metal-tætninger
- Til gasrenhed op til 6.0 (99.9999% renhed)
- Egnede til korrosive gasser
- Renset til oxygen service

Example for selecting a part number:

D43215	AR	O2	O5
BASIC SERIES	GAS	OUTLET CONNECTION	
D43215 - Brass D43216 - Stainless Steel Inlet Connections - G, 1/8" male Standard order of handle/rod and cap: Cory  Please reference distributor's "Point- of-Care" literature  Gas spec/ID, label acc. EN 13762 available on request	AR (BRASS) - Oxygen, all other non-corrosive gases  Attention: For CO or test gases including CO, please use Stainless Steel version  AK (Stainless Steel) - Corrosive Gases	O0 - Without G, 1/8" female O5 - Compression fitting # 8 mm with nozzle 6 mm O6 - Compression fitting tube G, 1/8" with nozzle	
		*Not available for D43216 Stainless Steel	

### Diaphragm Metering Valve with Wall Mounting Plate - Part Number Selector

Example for selecting a part number:

D43528	AR	O2	E
BASIC SERIES	GAS	OUTLET CONNECTION	INLET CONNECTION
D43528 - Brass D43529 - Stainless Steel	AR (BRASS) - Oxygen, all other non-corrosive gases  Attention: For CO or test gases including CO, please use Stainless Steel version  AK (Stainless Steel) - Corrosive Gases	O0 - Without G, 1/8" female O2 - Compression fitting tube G, 1/8" O5 - Compression fitting # 8 mm with nozzle 6 mm O6 - Compression fitting # 8 mm with nozzle 6 mm	E - Without G, 1/8" female F - Compression fitting # 8 mm G - Compression fitting # 10 mm
		*Not available for D43529 Stainless Steel	
		*Not available for D43528 Brass	



