

KEMISK INJECTION, SPRING LOADED, PISTON SENSOR

56-2000 Serien Trykreducerede regulator

56-2000
56-2000 serien

- Max indgangstryk: 1034 bar
- Max udgangstryk: 1034 bar
- Temperaturområde: -26 til 74°C
- CV: 0.06, 0.12
- Leak: Bubble-tight



PRODUKTBESKRIVELSE

Tescom 56-2000 Serien

Denne serie giver dig et meget nøjagtigt flow kontrol, som giver dig mulighed for at have et kontinuerligt injection rate over the life of the well.

Applikationer

- Offshore Chemical Injection

Fordele

Nøjagtigt og kontinuerligt flow kontrol som reducere riskoen for flowtab fra under og efter injection

Høj kvalitets piston-sensor komponenter som giver forlænget levetid i offshore applikationer og som reducere vedligeholdelse og unødigt downtime

Alternativ muligheder for fuld automatisk injection rate kontrol med ER5000

Example for selecting a part number:

56-20	8	0	D	6	9	D	2	7	0		
BASIC SERIES	MAXIMUM INLET PRESSURE (BODY MATERIAL)	MAXIMUM OUTLET PRESSURE (SPRING/BIAS PRESSURE)	SOFT GOODS MATERIAL	DYNAMIC RETO-SEALS	STATIC O-RINGS	BACK-UP RINGS	INLET AND OUTLET PORT TYPE	INLET AND OUTLET PORT SIZE	FLOW CAPACITY	MAIN VALVE AND VENT SEAL	GAUGE PORT OFFSETS
56-20	8 - 15,000 psig (1034 bar) (17.4 MPa)	0 - 200 15,000 psig (1034 bar) (17.4 MPa)	0 - Nitrile, Buna-N	Nitrile, Buna-N	PC 111	6 - Moduras 9 - 316L Pressure	2 - C ₁ + 0.06 3 - C ₁ + 0.12	7 - 1/2" NPT 3 - 1/2" NPT	0 - No gauge ports	0 - No gauge ports	

1. Pressure at which regulator is used must be compatible with the pressure rating of the regulator and part size/type provided.

All dimensions are reference & nominal
Metric (indicated) equivalent are in brackets