



## KAPILARRØRSTERMOMETER STANDARDUDFØRSEL

Serie IFC

IFC-14349092  
Ø60, 0-120°C, L=1m, glat 50x8mm

- Måleområde fra -100 til 400°C
- Husdiameter 63, 80, 100, 72x72 eller 96x96
- Hus i plast til panelmontage
- Kapillarrør op till 5m
- Kapillarrør i plast, kobber eller rustfrit stål






### PRODUKTBESKRIVELSE



### SPECIFIKATIONER

|                                      |                     |
|--------------------------------------|---------------------|
| Capillary length                     | 1000 mm             |
| Diameter                             | 60 mm               |
| Indstikslængde                       | 50 mm               |
| IP-klasse                            | IP54                |
| Material Capillary                   | Kobber plast dæksel |
| Materiale glas                       | Instrumentglas      |
| Materiale hus                        | Plast               |
| Materiale medieberørte del           | Messing             |
| Omgivelsestemperatur fra             | -20 °C              |
| Omgivelsestemperatur til             | 70 °C               |
| Plug diameter                        | 8 mm                |
| Temperature resistance of cable from | -40 °C              |
| Temperature resistance of cable to   | 120 °C              |
| Temperaturområde fra                 | 0 °C                |
| Temperaturområde til                 | 120 °C              |

# Standard version



**Standard version**  
 Plain stem (without thread), SF94  
 Copper alloy  
 Insertion length = variable  
 Stem diameter Ød = 6, 8, 8.5, 10 mm



**Rotatable connection with loose threaded connection**  
 SF911/DV19 M14 x 1.5, R 1/2, R 1/2, R 1/2  
 Copper alloy  
 Insertion length = variable  
 Stem diameter Ød = 6, 8, 8.5, 10 mm

