



AUER SIGNALHORN KLH/KDH

710100004

KLH mini horn 92dB 12V DC med tragt

- Membransummer
- IP43
- 88-92dB



PRODUKTBESKRIVELSE

Sirene til indendørs og udendørs brug. Anvendes f.eks. i industrien og havne, mindre og billig membransummer til indendørs brug.

SPECIFIKATIONER

Farve hus	Grå RAL 7035
IP-klasse	IP43, NEMA Type 2
Lydniveau max	92 dB
Forsyningsspænding	12 V
Forsyningsspænding DC max	13,2 V DC
Forsyningsspænding DC min	10,8 V DC
Montering	Vertikal
Nominal strøm max	0,055 A
Temperaturområde fra	-25 °C
Temperaturområde til	50 °C
Vægt	180 g
Tonefrekvens min	50 Hz
Antal toner	1 pc

Nominel strøm min.	0,055 A
Koblingsklemme	2,5 mm ²
Lydniveau min	92 dB
Tonefrekvens max	50 Hz
Kabel indgang	Bagsiden

The sound pressure decreases by 6 dB when doubling the distance: the following distance table is to be seen as indication, as also factors like tone type, wind speed, wind direction, humidity, weather conditions etc. do influence the sound pressure level.

Distance (m)	Sound pressure dB (A)																								
1	85	70	75	80	85	90	92	94	96	98	100	102	104	106	108	110	112	114	116	118	120				
2	59	64	69	74	79	84	86	88	90	92	94	96	98	100	102	104	106	108	110	112	114				
3	55	60	65	70	75	80	82	84	86	88	90	92	94	96	98	100	102	104	106	108	110				
5	51	56	61	66	71	76	78	80	82	84	86	88	90	92	94	96	98	100	102	104	106				
10	45	50	55	60	65	70	72	74	76	78	80	82	84	86	88	90	92	94	96	98	100				
20	39	44	49	54	59	64	66	68	70	72	74	76	78	80	82	84	86	88	90	92	94				
30	35	40	45	50	55	60	62	64	66	68	70	72	74	76	78	80	82	84	86	88	90				
50	30	35	40	45	50	55	58	60	62	64	66	68	70	72	74	76	78	80	82	84	86				
100		25	30	35	40	45	50	52	54	56	58	60	62	64	66	68	70	72	74	76	78	80			
200			20	25	30	35	40	42	44	46	48	50	52	54	56	58	60	62	64	66	68	70	72	74	
500				15	20	25	30	32	34	36	38	40	42	44	46	48	50	52	54	56	58	60	62	64	66

The sound pressure decreases by 6 dB when doubling the distance

