

EFFEPI 3-VEJS KUGLEVENTILER "T" BORRET KUGLE TYPE F3T

EFFF3T15SA

Kemi messing 3-vejs kugleventil DN15 double acting

- Materiale: Messing OT58 nikkel belagt
- Medier: Gas, Olie, Væske
- Størrelser: DN15 - DN50
- Fås med pneumatisk aktuator
- Temperaturområde: -15°C - +100°C



PRODUKTBESKRIVELSE

Messing 3-vejs kugleventil med roterende pneumatisk aktuator.

Ventilkrop: Messing OT58 nikkel belagt.

Kugle: Messing OT58 heavy duty forkromet.

Pakning: Virgin PTFE

Funktioner: 3-vejs (2 positioner)

Temperaturområder:

-15°C - +100°C

Max temperatur for special brug (ventil fuldt open):

+100°C brændstofs olier, mineral olier og mageriner

+90°C hav og drikkevand

+60°C trichlorethylen, butan, methan, propan, carbon dioxido

+40°C Alkohol, benzin, lette gasser, naturlige gasser, lime vand, sodavand.

Aktuator tryk:

Double acting fra 4 - 8 bar

Single acting fra 6 - 8 bar

Tilslutninger med GAS ISO228 hun-hun fittings.

Kan leveres med NPT-forbindelser

GAS tilslutning 1/8"

DA: 1/2" - 3/4" - 1" - 1"1/4 - 1"1/2 - 2" (double acting)


SA: 1/2" - 3/4" - 1" - 1"1/4 - 1"1/2 - 2" (single acting)

Anodiserende behandlet udvendigt i aluminium

DOUBLE ACTING										
IN.	S.	ACTING	A	B	C	D	E	F	WEIGHT	Wt. WEIGHT
mm.	Type	mm.	mm.	mm.	mm.	mm.	mm.	mm.	mm.	kg.
5	1/2"	DE010	225	200	80	10	10	10	10	1.5
10	3/4"	DE030	337	270	100	10	10	10	10	1.5
15	1"	DE050	411	320	120	10	10	10	10	1.5
20	1 1/2"	DE070	475	370	140	10	10	10	10	1.5
25	1 3/4"	DE090	538	420	160	10	10	10	10	1.5
30	2"	DE110	602	470	180	10	10	10	10	1.5
40	2 1/2"	DE130	727	570	220	10	10	10	10	1.5
50	3"	DE150	852	670	260	10	10	10	10	1.5


SINGLE ACTING										
IN.	S.	ACTING	A	B	C	D	E	F	WEIGHT	Wt. WEIGHT
mm.	Type	mm.	mm.	mm.	mm.	mm.	mm.	mm.	mm.	kg.
5	1/2"	SE010	225	200	80	10	10	10	10	1.5
10	3/4"	SE030	337	270	100	10	10	10	10	1.5
15	1"	SE050	411	320	120	10	10	10	10	1.5
20	1 1/2"	SE070	475	370	140	10	10	10	10	1.5
25	1 3/4"	SE090	538	420	160	10	10	10	10	1.5
30	2"	SE110	602	470	180	10	10	10	10	1.5
40	2 1/2"	SE130	727	570	220	10	10	10	10	1.5
50	3"	SE150	852	670	260	10	10	10	10	1.5

OVERALL DIMENSIONS




T - DRILLED BALL

ASSEMBLY 1-2



Direct passage 1-2 Right deviation 1-3

ASSEMBLY 2-1



Left Deviation 2-3 Direct passage 1-2

RATED PRESSURE "PN"

G	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"
PN	40	40	25	16	16	16