

EFFEPI 3-VEJS LAVTRYKS KUGLEVENTILER TYPE F3D

EFFF3D15SA

Kemi messing 3-vejs kugleventil DN15 single acting

- Materiale: Messing OT58 nikkel belagt
- Medier: Gas, Olie, Væske
- Størrelser: DN15 - DN50
- Fås med pneumatisk aktuator
- Temperaturområde: -15°C - +100°C



PRODUKTBESKRIVELSE

Messing 3-vejs kugleventil med roterende pneumatisk aktuator.

Ventilkrop: Messing OT58 nikkel belagt.

Kugle: Messing OT58 heavy duty forkromet.

Pakning: Virgin PTFE

Funktioner: 3-vejs (2 positioner)

Temperaturområder:

-15°C - +100°C

Max temperatur for special brug (ventil fuldt open):

+100°C brændstofs olier, mineral olier og mageriner

+90°C hav og drikkevand

+60°C trichlorethylen, butan, methan, propan, carbon dioxido

+40°C Alkohol, benzin, lette gasser, natur gasser, lime vand, sodavand.

Aktuator tryk:

Double acting fra 3 - 8 bar

Single acting fra 5 - 8 bar

Tilslutninger med GAS ISO228 hun-hun fittings.

Kan leveres med NPT-forbindelser

GAS tilslutning 1/8"

DA: 1/2" - 3/4" - 1" - 1"1/4 - 1"1/2 - 2" (double acting)



SA: 1/2" - 3/4" - 1" - 1"1/4 - 1"1/2 - 2" (single acting)

Anodiserende behandlet udvendigt i aluminium

DOUBLE ACTING										
DN	B	A	B	C	D	E	F	Weight	Wt	
mm	Type	mm	mm	mm	mm	mm	mm	mm	kg/lb	
15	1/2"	202	200	197	89	75	15	15	23	5
20	3/4"	252	250	249	117	101	17	17	42	9
25	1"	302	300	299	145	127	19	19	61	13
32	1 1/4"	352	350	349	173	153	21	21	79	17
40	1 1/2"	402	400	399	201	179	23	23	93	20
50	2"	452	450	449	229	205	25	25	117	26

SINGLE ACTING										
DN	B	A	B	C	D	E	F	Weight	Wt	
mm	Type	mm	mm	mm	mm	mm	mm	mm	kg/lb	
15	1/2"	202	200	197	89	75	15	15	23	5
20	3/4"	252	250	249	117	101	17	17	42	9
25	1"	302	300	299	145	127	19	19	61	13
32	1 1/4"	352	350	349	173	153	21	21	79	17
40	1 1/2"	402	400	399	201	179	23	23	93	20
50	2"	452	450	449	229	205	25	25	117	26

OVERALL DIMENSIONS



RATED PRESSURE "PN"						
G	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"
PN	10	10	10	10	10	10