

EFFEPI RUSTFRI STÅL KUGLEVENTILER TYPE "AL" AISI 304

EFFAL10DA

Kemi rustfri stål kugleventil DN10 double acting
AISI304

- Materiale: Rustfri stål AISI 304
- Medier: Gas, Olie, Væske
- Størrelser: DN10 - DN100 (DA) DN10 - DN50 (SA)
- Fås med pneumatisk aktuator
- Temperaturområde: -15°C - +100°C



PRODUKTBESKRIVELSE

Rustfri stål kugleventil med roterende pneumatisk aktuator.

Ventilkrop: Rustfri stål AISI304

Kugle: Rustfri stål AISI304

Pakning: Virgin PTFE

Temperaturområder:

-15°C - +100°C

Max temperatur for special brug (med fuldt åben ventil):

+100°C brændstofs olier, mineral olier og mageriner

+90°C hav og drikkevand

+60°C trichlorethylen, butan, metan, propan, carbon dioxide

+40°C Alkohol, benzin, lette gasser, naturlige gasser, lime vand, sodavand.

Aktuator tryk:

Double acting fra 3 - 8 bar

Single acting fra 6 - 8 bar

Tilslutninger med GAS ISO228 hun-hun fittings.

Kan leveres med NPT eller DIN tilslutning

GAS tilslutning 1/8"

DA: 3/8" - 1/2" - 3/4" - 1" - 1"1/4 - 1"1/2 - 2" - 2"1/2 - 3" - 4" (double acting)


SANC: 3/8" - 1/2" - 3/4" - 1" - 1"1/4 - 1"1/2 - 2" (single acting normally closed)

SANO: 3/8" - 1/2" - 3/4" - 1" - 1"1/4 - 1"1/2 - 2" (single acting normally open)

Anodiserende behandlet udvendigt i aluminium

DOUBLE ACTING											OVERALL DIMENSIONS
DN	G	AS2428	A	B	C	D	E	stroke	V ₁	Weight	
mm		type	mm	mm	mm	mm	mm	mm	liters	kg	
10	3/8"	DS502	210	95	12	40	43	25	40	104	
15	1/2"	DS502	270	108	12	50	53	32	70	203	
20	3/4"	DS502	280	120	12	60	63	37	100	302	
25	1"	DS502	290	135	12	70	73	43	140	401	
32	1 1/4"	DS603	280	150	12	80	83	50	180	500	
40	1 1/2"	DS603	290	165	12	90	93	57	240	699	
50	2"	DS603	310	180	12	100	103	63	300	898	
63	2 1/2"	DS704	300	200	12	110	113	70	370	1097	
80	3"	DS805	320	220	12	120	123	77	450	1296	
100	4"	DS906	340	240	12	130	133	85	530	1495	

SINGLE ACTING (NC-NO)										
DN	G	AS2428	A	B	C	D	E	stroke	V ₁	Weight
mm		type	mm	mm	mm	mm	mm	mm	liters	kg
10	3/8"	SS502	210	95	12	40	43	25	40	104
15	1/2"	SS502	270	108	12	50	53	32	70	203
20	3/4"	SS282	280	120	12	60	63	37	100	302
25	1"	SS282	290	135	12	70	73	43	140	401
32	1 1/4"	SS603	280	150	12	80	83	50	180	500
40	1 1/2"	SS603	290	165	12	90	93	57	240	699
50	2"	SS603	310	180	12	100	103	63	300	898
63	2 1/2"	SS704	300	200	12	110	113	70	370	1097
80	3"	SS805	320	220	12	120	123	77	450	1296
100	4"	SS906	340	240	12	130	133	85	530	1495



RATED PRESSURE "PN"										
G	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"	4"
PN	64	64	64	40	40	40	25	25	25	25