

EFFEPI RUSTFRI STÅL KUGLEVENTIL TYPE "AL1" AISI 316

EFFAL110DA

Kemi rustfri stål kugleventil DN10 double acting
AISI316

- Materiale: Rustfri stål AISI 316
- Medier: Gas, Olie, Væske
- Størrelser: DN10 - DN100 (DA) DN10 - DN50 (SA)
- Fås med pneumatisk aktuator
- Temperaturområde: -15°C - +100°C



PRODUKTBESKRIVELSE

Rustfri stål kugleventil med roterende pneumatisk aktuator.

Ventilkrop: Rustfri stål AISI316

Kugle: Rustfri stål AISI316

Pakning: Virgin PTFE

Temperaturområder:

-15°C - +100°C

Max temperatur for special brug (med fuldt åben ventil):

+100°C brændstofs olier, mineral olier og mageriner

+90°C hav og drikkevand

+60°C trichlorethylen, butan, methan, propan, carbon dioxide

+40°C Alkohol, benzin, lette gasser, naturlige gasser, lime vand, sodavand.

Aktuator tryk:

Double acting fra 3 - 8 bar

Single acting fra 6 - 8 bar

Tilslutninger med GAS ISO228 hun-hun fittings.

Kan leveres med NPT eller DIN tilslutning

GAS tilslutning 1/8"

DA: 3/8" - 1/2" - 3/4" - 1" - 1 1/4" - 1 1/2" - 2" - 2 1/2" - 3" - 4" (double acting)

SANC: 3/8" - 1/2" - 3/4" - 1" - 1 1/4" - 1 1/2" - 2" (single acting normally closed)

SANO: 3/8" - 1/2" - 3/4" - 1" - 1 1/4" - 1 1/2" - 2" (single acting normally open)

Anodiserende behandlet udvendigt i aluminium

DOUBLE ACTING												OVERALL DIMENSIONS
DN	G	40/38	A	B	C	D	E	mm	F ₁	mm	Weight	
mm	Type	mm	mm	mm	mm	mm	mm	mm	mm	mm	kg	
10	3/8"	SP502	210	70	12	10	45	25	17	152		
15	1/2"	SP502	275	90	12	10	45	32	20	203		
20	1"	SP502	330	110	12	10	45	32	20	253		
25	1 1/4"	SP502	390	130	12	10	45	32	20	303		
32	1 1/2"	SP502	450	150	12	10	45	32	20	353		
40	2"	SP502	510	170	12	10	45	32	20	403		
50	2 1/2"	SP502	570	190	12	10	45	32	20	453		
63	3"	SP502	630	210	12	10	45	32	20	503		
80	3 1/2"	SP502	690	230	12	10	45	32	20	553		
100	4"	SP502	750	250	12	10	45	32	20	603		
125	5"	SP502	810	270	12	10	45	32	20	653		
160	6"	SP502	870	290	12	10	45	32	20	703		

SINGLE ACTING (NC-40)												OVERALL DIMENSIONS
DN	G	40/38	A	B	C	D	E	mm	F ₁	mm	Weight	
mm	Type	mm	mm	mm	mm	mm	mm	mm	mm	mm	kg	
10	3/8"	SP502	210	70	12	10	45	25	17	152		
15	1/2"	SP502	275	90	12	10	45	32	20	203		
20	1"	SP502	330	110	12	10	45	32	20	253		
25	1 1/4"	SP502	390	130	12	10	45	32	20	303		
32	1 1/2"	SP502	450	150	12	10	45	32	20	353		
40	2"	SP502	510	170	12	10	45	32	20	403		
50	2 1/2"	SP502	570	190	12	10	45	32	20	453		
63	3"	SP502	630	210	12	10	45	32	20	503		
80	3 1/2"	SP502	690	230	12	10	45	32	20	553		
100	4"	SP502	750	250	12	10	45	32	20	603		
125	5"	SP502	810	270	12	10	45	32	20	653		
160	6"	SP502	870	290	12	10	45	32	20	703		

RATED PRESSURE "PN"											
G	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"	4"	
PN	64	64	64	40	40	40	25	25	25	25	