

EFFEPI SKRÅSÆDEVENTIL TYPE "D"

EFFD15DA

Kemi skråsædeventil DN15 double acting

- Materiale: Bronze ventil - Aktuator Aluminium
- Disk: Messing
- Størrelser: DN15 - DN80
- Fås med Pneumatisk aktuator
- Pakninger: NBR, FPM, EPDM, PTFE(PTFE+FPM)



PRODUKTBESKRIVELSE

Bronze skråsædeventil med flad lukke skive

Lufttæt lukning

Fås med Pneumatisk aktuator med mulighed for 360° montering med positions bolt.

Pakninger: NBR, FPM, EPDM, PTFE(PTFE+FPM)

Tilslutninger med GAS ISO228 hun-hun fittings.

Kan leveres med NPT-tilslutninger

GAS tilslutning 1/8"

Temperaturområder:

NBR pakning: -20°C - +100°C

FPM pakning: -15°C - +150°C

EPDM pakning: -40°C - +100°C

Aktuator tryk:

Max tryk aktuator: 8 bar.

Versioner og størrelser:

DA: 1/2" - 3/4" - 1" - 1.1/4" - 1.1/2" - 2" - 2.1/2" - 3" (double acting)

SANC: 1/2" - 3/4" - 1" - 1.1/4" - 1.1/2" - 2" - 2.1/2" - 3" (single acting normally closed)

SANO: 1/2" - 3/4" - 1" - 1.1/4" - 1.1/2" - 2" (single acting normally open)

Anodiserende behandlet udvendigt i aluminium

Art. "D"

DIFFERENTIAL PRESSURE CHARTS

NC - NBR-FFM-EPDM			NC - PTFE			DA/NO - NBR-FFM-EPDM			DA/NO - PTFE		
G	DIFF.P		G	DIFF.P		G	PILOT	DIFF.P	G	PILOT	DIFF.P
bar	psi		bar	psi		bar	PRESS	bar	bar	PRESS	bar
1/2"	20	1/2"	20	1/2"	3	1/2"	3	14	1/2"	3	12
3/4"	20	3/4"	20	1/2"	4	1/2"	4	20	1/2"	4	18
1"	18	1"	18	3/4"	3	3/4"	3	13	3/4"	3	11
1 1/4"	18	1 1/4"	18	3/4"	4	1"	3	10	1"	3	8
1 1/2"	15	1 1/2"	15	1"	4	1 1/4"	3	12	1 1/4"	3	12
2"	15	2"	15	1 1/4"	4	1 1/2"	3	12	1 1/2"	3	10
2 1/2"	15	2 1/2"	15	1 1/2"	4	1 1/2"	4	15	1 1/2"	4	18
3"	15	3"	15	2"	3	2"	3	8	2"	3	7
				2"	4	2"	4	10	2"	4	8
				2 1/2"	4	2 1/2"	4	5	2 1/2"	4	5
				2 1/2"	3	2 1/2"	3	8	2 1/2"	3	7
				3"	4	3"	4	5	3"	4	3
				3"	5	3"	5	5	3"	5	5



OVERALL DIMENSIONS DA/NO VERSION

UN	G	A	B	C	d	E	F	WV03	K1	W032
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm
15	1/2"	26	45.5	41	26	43	13	27	4.5	45
20	3/4"	32	52	50	30	45	13	33	5	50
25	1"	38	57	41	35	45	15	38	5	55
30	1 1/4"	45	65	55	40	50	15	45	5	60
40	1 1/2"	57	77	66	45	55	15	55	5	70
50	2"	70	92	78	55	65	15	65	5	85
65	2 1/2"	88	110	97	65	75	15	80	5	105
80	3"	108	130	115	75	85	15	95	5	130

OVERALL DIMENSIONS NC VERSION

UN	G	A	B	C	d	E	F	WV03	K1	W032
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm
15	1/2"	26	45.5	41	26	43	13	27	4.5	45
20	3/4"	32	52	50	30	45	13	33	5	50
25	1"	38	57	41	35	45	15	38	5	55
30	1 1/4"	45	65	55	40	50	15	45	5	60
40	1 1/2"	57	77	66	45	55	15	55	5	70
50	2"	70	92	78	55	65	15	65	5	85
65	2 1/2"	88	110	97	65	75	15	80	5	105
80	3"	108	130	115	75	85	15	95	5	130

