



JUSTERBAR BAJONETFØLER TIL PLASTINDUSTRIEN

Serie TC47-AB

TC47-AB
Justerbar bajonettføler

- Måleområde fra -40 op til 750 °C
- Type J, L, K eller T (andre efter behov)
- Design med fjeder eller forstærkning
- Føleren kan justeres til egnet længde ved installation
- Meget let at skifte



PRODUKTBESKRIVELSE SPECIFIKATIONER

Temperaturområde fra	-40 °C
Temperaturområde til	750 °C

Adjustable bayonet ■ Spring up to 200 mm or 8" of adjustability ■ Armour full length of adjustability	Lead wire ■ Fibreglass / fibreglass ■ PTFE / PTFE ■ PVC / PVC ■ Kapton / Kapton ■ Others on request
Junction ■ Grounded (unisolated) ■ Ungrounded (isolated)	Lead wire covering ■ None ■ Stainless steel overbraid (no tracer) ■ Stainless steel overbraid (with tracer) ■ Tin copper overbraid ■ Interlocking flexible armour
Tip diameter (Ø) ■ 3/16" ■ 1/4" ■ 3/8" ■ 4 mm ■ 6 mm ■ 8 mm ■ 10 mm ■ Others on request	Termination at lead end ■ Bare ends ■ Standard thermo plug 2-pin (male) ■ Miniature thermo plug 2-pin (male) ■ Standard plug with cable clamp (male) ■ Miniature plug with cable clamp (male) ■ Lemosa plug size 15 (male) ■ Lemosa plug size 25 (male) ■ Screw-in plug, Binder (male) ■ Others on request
Probe length ■ Standard ■ Others on request	Calibration type ■ J ANSI MC96.1 red Ø white Ø ■ K ANSI MC96.1 red Ø yellow Ø ■ T ANSI MC96.1 red Ø blue Ø ■ J IEC 584-3 white Ø black Ø ■ K IEC 584-3 white Ø green Ø ■ T IEC 584-3 white Ø brown Ø ■ J DIN 43714 blue Ø red Ø ■ K DIN 43714 green Ø red Ø ■ T DIN 43714 brown Ø red Ø ■ Others on request
Bayonet cap Id Ø Fits bayonet adapter ■ Single slot 11.4 mm (7/16") 11 mm O.D. ■ Double slot 15.4 mm (7/16") 11 mm O.D. ■ Double slot 12.2 mm (3/16") 12 mm O.D. ■ Double slot 14.2 mm (9/16") 12 mm O.D. ■ Double slot 15.2 mm (19/32") 15 mm O.D. ■ Others on request	
Lead length ■ 500 mm ■ 1000 mm ■ 1500 mm ■ 2000 mm ■ 2500 mm ■ Others on request	