



FØLER MED GEVIND TIL PLASTINDUSTRIEN

TC47-NT

TC47-NT
Føler med gevind

- Måleområde fra -40 op til 750°C
- Type J, L, K eller T (andre efter behov)
- Forlængerkabel i eksempelvis PTFE, fiberglas eller PVC
- Fikseret forudbestemt længde og monteres direkte i processen
- Meget let at skifte



PRODUKTBESKRIVELSE

SPECIFIKATIONER

Temperaturområde fra	-40 °C
Temperaturområde til	750 °C

Nozzle bolt material

- Stainless steel
- Brass
- Others on request

Junction

- Grounded (unisolated)
- Ungrounded (isolated)

Nozzle bolt thread size

- 1/4 x 28
- M5
- M8
- Others on request

Lead length

- 500 mm
- 1000 mm
- 1500 mm
- 2000 mm
- 2500 mm
- Others on request

Lead wire

- Fibreglass / Fibreglass
- PTFE / PTFE
- PVC / PVC
- Kapton / Kapton
- Others on request

Lead wire covering

- None
- Stainless steel overbraid (no tracer)
- Stainless steel overbraid (with tracer)
- Tin copper overbraid

Termination at lead end

- Bare ends

Standard thermo plug 2-pin (male)

Miniature thermo plug 2-pin (male)

Standard plug with cable clamp (male)

Miniature plug with cable clamp (male)

Lead wire plug size 15 (male)

Lead wire plug size 25 (male)

Screw-in plug, Binder (male)

- Others on request

Calibration type

■ J	ANSI MC96.1	red Ø	white Ø
■ K	ANSI MC96.1	red Ø	yellow Ø
■ T	ANSI MC96.1	red Ø	blue Ø
■ J	IEC 584-3	white Ø	black Ø
■ K	IEC 584-3	white Ø	green Ø
■ T	IEC 584-3	white Ø	brown Ø
■ J	DRN 43714	blue Ø	red Ø
■ K	DRN 43714	green Ø	red Ø
■ T	DRN 43714	brown Ø	red Ø
■ Others on request			